


**empack**Empack Spraytech Inc.  
98 Walker Drive  
Brampton, Ontario, L6T 4H6  
Canada  
905-792-6571**PRODUCT: Emzone SAR 707 Foam and Fabric Adhesive - 454g****CODE: P8-088177****SECTION 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product Identity..... Emzone SAR 707 Foam and Fabric Adhesive - 454g  
 Product Item Numbers..... P8-088177  
 Manufacturer..... Empack Spraytech Inc.  
 98 Walker Drive  
 Brampton  
 Ontario  
 Canada  
 L6T 4H6  
 905-792-6571  
 24 hour emergency telephone number..... In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800) 424-9300.  
 Recommended Use..... Adhesive .

**SECTION 02: HAZARDS IDENTIFICATION**

Label Elements:  
 Signal Word..... WARNING.  
 Hazard Classification:  
 Physical Hazards..... Flammable Aerosols - Category 2. Gases Under Pressure - Liquefied Gas .  
 Health Hazards..... Acute Toxicity Oral - Category 4. Skin Irritation - Category 2. Eye Damage/Irritation - Category 2A. Carcinogenicity - Category 2. Specific Target Organ Toxicity, Single Exposure - Category 3. Specific Target Organ Toxicity, Repeated Exposure - Category 2.  
 Hazard Statement..... Flammable aerosol. Pressurized container: may burst if heated. Contains gas under pressure; may explode if heated. Harmful if swallowed . Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.  
 Precautionary Statements:  
 Prevention..... Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash hand thoroughly after handling. Do not eat, drink, or smoke when using this product. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapours/spray.  
 Response..... IF SWALLOWED: Immediately call a POISON CENTER. Rinse mouth. IF ON SKIN: Wash with plenty of soap and water. If Skin Irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER if you feel unwell. Get medical advice/attention if you feel unwell.  
 Storage..... Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. Store locked up.  
 Disposal..... Dispose of contents/ container in accordance with local/regional/national/international regulations.  
 Hazard(s) not otherwise classified (HNOC) None Known.

**SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS**

HAZARDOUS INGREDIENTS	CAS #	WT. %
Dichloromethane	75-09-2	45-70
Isobutane	75-28-5	10-30
Propane	74-98-6	10-30

PRODUCT: Emzone SAR 707 Foam and Fabric Adhesive - 454g

CODE: P8-088177

**SECTION 04: FIRST AID MEASURES**

Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance. If breathing is difficult, give oxygen and get medical attention.
Eye Contact.....	Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs. Get medical attention if irritation persists. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids.
Skin Contact.....	Immediately flush the contaminated skin with soap and water. If this chemical penetrates clothing, immediately remove the clothing and flush the skin with water. If irritation persists after washing, get medical attention. Remove contaminated clothing. Launder clothing before reuse. If irritation occurs consult with your doctor.
Ingestion.....	Not likely to be ingested. If occurs, do not give anything by mouth to an unconscious person. Do not induce vomiting, get medical attention. Obtain medical advice.
Most important symptoms/effects, acute .. and delayed	Direct eye contact may cause temporary eye irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**SECTION 05: FIRE FIGHTING MEASURES**

Suitable Extinguishing Media.....	Dry chemical powder. Carbon dioxide. Foam, water spray or fog.
Unsuitable Extinguishing Media.....	Do not use water jet as an extinguisher, as this will spread the fire.
Specific Hazards Arising from the Chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special Protective Equipment and ..... Precautions for Firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from immediate hazard area if it is safe to do.
General Fire Hazards.....	Flammable.

**SECTION 06: ACCIDENTAL RELEASE MEASURES**

Personal Precautions, Protective ..... Equipment and Emergency Procedures	Ensure adequate ventilation; avoid formation of dust. Wear protective equipment and keep unprotected persons away. Use respiratory protection against the effects of dust.
Methods and Materials for Containment .. and Cleaning Up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.
Environmental Precautions.....	Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

**SECTION 07: HANDLING AND STORAGE**

Precautions for Safe Handling.....	Wash thoroughly after handling. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Avoid contact with eyes. Avoid breathing vapours or spray mists of this product. Use with adequate ventilation. Keep away from heat, sparks, and open flames.
Conditions for Safe Storage including any Incompatibilities	Store in a cool, dry, well-ventilated area away from incompatible substances. Do not store in direct sunlight. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	ACGIH TLV		OSHA PEL	NIOSH
	TWA	STEL		
Dichloromethane	50 ppm (8 hrs)	Not available	25 ppm (8 hrs)	125 ppm (15 minutes)
Isobutane	Not available	1,000 ppm	Not available	Not available
Propane	Not available	Not available	1,000 ppm	Not available
Appropriate Engineering Controls.....	Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved. Ground all equipment and cylinders before use.			
Individual Protection Measures: Eye/Face Protection.....	Prevent eye contact, wear safety glasses in the event that eye contact is possible.			

PRODUCT: Emzone SAR 707 Foam and Fabric Adhesive - 454g

CODE: P8-088177

**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Skin Protection.....	Normally, no hand protection is required; however, prolonged or repeated contact with skin use chemical resistant gloves conforming to appropriate regulations. Observe the instructions regarding permeability and breakthrough time that are provided by the supplier of the gloves. Use rubber or latex gloves when there is a potential for prolonged or excessive skin contact.
Respiratory Protection.....	Use approved NIOSH respirators for emergencies. Typical use of this product under normal conditions does not require the use of respiratory protection. If airborne concentrations are above the applicable exposure limits (listed below), use NIOSH approved respiratory protection .
Thermal Hazards.....	None Known.
General Hygiene Considerations.....	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.

**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Physical State.....	Aerosol.
Physical Appearance.....	Yellow.
Odour.....	No odour.
Odour Threshold (ppm).....	Not available.
pH.....	Not applicable.
Vapour Pressure (psig).....	60-75 .
Vapour Density (Air=1).....	>1.
Evaporation Rate (n-Butyl Acetate = 1).....	Not available.
Boiling Point (Propellant), ° C.....	-11.72°C (10.9°F).
VOC Content.....	Not available.
Specific Gravity (Liquid).....	1.225.
Specific Gravity (Aerosol).....	1.022.
Solubility in water.....	Slightly soluble.
Auto Ignition Temperature (°C).....	556°C (1032.8 °F). (Propellant).
Flash Point (°C), Method.....	-104 °C (-156°F). Estimated. (Propellant).
Flashback.....	No.
Lower Explosive Limit (% vol).....	1.8. (Propellant).
Upper Explosive Limit (% vol).....	9.5. (Propellant).

**SECTION 10: STABILITY AND REACTIVITY**

Reactivity .....	Product not reactive under normal conditions of use.
Chemical Stability.....	Stable at normal temperatures and pressures.
Possibility of Hazardous Reactions.....	Will not occur.
Conditions to Avoid.....	Avoid sources of heat and flame, and electrostatic charge.
Incompatible Materials.....	Avoid contacting with oxidizers.
Hazardous Decomposition Products.....	No hazardous decomposition products when stored and handled correctly.

**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Dichloromethane	76 mg/L (Rat - 4hrs)	985 mg/kg (Oral - Rat)
Isobutane	658 mg/L (Rat - 4hrs)	Not available
Propane	658 mg/L (Rat - 4hrs)	Not available
Information on Likely Routes of Exposure:		
Routes of entry - Inhalation.....	No.	
Routes of entry - Skin & Eye.....	Yes.	
Routes of entry - Ingestion.....	Yes.	
Routes of entry - Skin Absorption.....	No.	
Symptoms Related to the Physical, .....	Irritant effects.	
Chemical and Toxicological Characteristics		
Acute Toxicity.....	Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.	
Skin Corrosion/Irritation.....	Causes skin irritation.	
Serious Eye Damage/Eye Irritation.....	Direct contact with eyes causes temporary irritation.	
Respiratory or Skin Sensitization.....	Inhalation may cause respiratory tract irritation. May cause skin sensitization.	
Germ Cell Mutagenicity.....	No information is available, and no adverse effects are expected.	
Carcinogenicity.....	Has been classified as a carcinogen by IARC.	
Reproductive Toxicity.....	No information is available.	
STOT - Single Exposure.....	Specific target organ toxicity single exposure Category 3. May cause drowsiness and dizziness.	

PRODUCT: Emzone SAR 707 Foam and Fabric Adhesive - 454g

CODE: P8-088177

**SECTION 11: TOXICOLOGICAL INFORMATION**

STOT - Repeated Exposure..... Specific Target Organ, Repeated Exposure- Category 2.  
 Aspiration Hazard..... No data available .  
 Chronic Effects..... No long term chronic effects are known or anticipated.

**SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicity..... May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment. This product contains the following substance which may also be hazardous for the environment: Methylene Chloride: Toxicity to fish: LC50 193 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: EC50 1682 mg/L, 48 hrs; Toxicity to algae: EC50 >662 mg/L, 96 hrs.  
 Bioaccumulation Potential..... The product itself has not been tested.  
 Mobility in Soil..... The product itself has not been tested.  
 Other Adverse Effects..... None Known.  
 Persistence and degradability ..... The product itself has not been tested.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

**SECTION 14: TRANSPORT INFORMATION**

TDG (Canada- Road)..... UN1950, AEROSOLS, Class 2.1.  
 DOT (US-Road)..... UN1950, AEROSOLS, Class 2.1, LTD QTY, Consumer Commodity ORM-D.  
 IMDG (International- Marine)..... UN1950, AEROSOLS, Class 2.1.  
 IATA (International- Air)..... UN1950, AEROSOLS, Class 2.1, LTD QTY.

**SECTION 15: REGULATORY INFORMATION**

Canada Regulations:..... WHMIS Classification. D2B: Material causing other toxic Materials.  
 US Regulations..... OSHA (29CFR 1910.1200).  
 California Proposition 65..... \*WARNING: This product contains a chemical known to the State of California to cause cancer. (Dichloromethane).

**SECTION 16: OTHER INFORMATION**

Disclaimer..... This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. . The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material.  
 Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.  
 Prepared by ..... Regulatory Affairs  
 Latest Revision ..... JUL 12/2018