

**empack**Empack Spraytech Inc.  
98 Walker Drive  
Brampton, Ontario, L6T 4H6  
Canada  
905-792-6571**PRODUCT: Emzone 12A A/C System Conditioner - 114g****CODE: 045855****Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product Identity..... Emzone 12A A/C System Conditioner - 114g  
 Product Item Numbers..... 045855  
 Manufactured by..... Empack Spraytech Inc.  
 98 Walker Drive  
 Brampton  
 Ontario  
 Canada  
 L6T 4H6  
 905-792-6571  
 24 hour emergency telephone number..... CANUTEC: (613)-996-6666 collect.  
 Recommended Use..... Repairs and conditions O-Rings Seals.  
 Consumer Commodity..... Yes.  
 Hazard Ratings:  
 HMIS..... Health: 1 Fire: 4 Reactivity: 1.  
 NFPA Rating..... Health: 1 Fire: 4 Reactivity: 1.

**Section 02: HAZARDS IDENTIFICATION**

Emergency Overview..... Extremely flammable . Container is under pressure. Container may explode if heated. Do not puncture. Do not burn. Do not get in eyes or clothing. Contact with liquid can cause frostbite . KEEP OUT OF REACH OF CHILDREN .

Potential Health Effects:  
 Skin Contact..... Contact with liquid may cause burns and frostbite. Skin may be flushed; as frostbite develops. Blisters may develop.  
 Eye Contact..... Direct contact with liquid or frost particles may produce severe and possibly permanent eye damage.  
 Ingestion..... Ingestion is not a likely route of exposure.  
 Inhalation..... Prolong Inhalation of content may cause irritation. Can cause headaches, dizziness, fatigue, lack of coordination, tremors and unconsciousness. May cause anemia irregular rhythm, respiratory arrest death at elevated exposure.

**Section 03: COMPOSITION/INFORMATION ON INGREDIENTS**

Hazardous Ingredients	CAS #	Wt. %
Isobutane	75-28-5	30- 60
Propane	74-98-6	30- 60
Conditioner	Trade secret	10-30
High temperature lubricant	Trade secret	1-5

**Section 04: FIRST AID MEASURES**

Eye Contact..... If eye tissue is frozen, seek medical attention immediately. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation, pain, swelling, lacrimation, or photophobia persist, get medical attention as soon as possible .

Skin Contact..... If frostbite has occurred, seek medical attention immediately; do NOT rub the affected areas or flush them with water. In order to prevent further tissue damage, do NOT attempt to remove frozen clothing from frostbitten areas. If frostbite has NOT occurred, immediately and thoroughly wash contaminated skin with soap and water.

Ingestion..... If swallowed, get medical attention immediately. Do not induce vomiting .

Inhalation..... Move victim to fresh air. If breathing has stopped, give artificial respiration. If heartbeat absent, give external cardiac compression. Monitor breathing and pulse. Get medical attention.

Additional Information..... Note to the doctor; treat symptomatically.

**Section 05: FIRE FIGHTING MEASURES**

Flammability Class..... Extremely Flammable.  
 Extinguishing Media..... Carbon dioxide, dry chemicals, foam or water fog.  
 Sensitivity to Mechanical Impact..... Not expected to be sensitive.  
 Sensitivity to Static Discharge..... Not expected to be sensitive.

PRODUCT: Emzone 12A A/C System Conditioner - 114g

CODE: 045855

**Section 06: ACCIDENTAL RELEASE MEASURES**

Spills and Leaks..... Remove all sources of ignition. Evacuate and Ventilate the area. Attempt to disperse the gas or direct its flow to a safe location for example by using fog sprays.

**Section 07: HANDLING AND STORAGE**

Handling..... Avoid breathing vapours or spray mists of this product. Avoid contact with eyes, skin, and clothing. Keep away from heat, sparks, and open flames. Keep container tightly closed. Use in well ventilated area. Do not store near cylinders, containing compressed Oxygen or other strong oxidizers. Wash thoroughly after handling . Remove ignition sources.

**Section 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Eye/Type..... Safety glasses with side-shields.  
 Skin/Type..... Use gloves and protective clothing against cold temperature made from viton, butyl rubber, PVC, neoprene or nitrile.  
 Respiratory/Type..... Not required on a short-term basis or if exhaust ventilation is provided. Use approved NIOSH respirators for emergencies.  
 Engineering Controls..... Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved.

## Exposure Limits

Ingredients	TWA	ACGIH TLV		PEL	OSHA PEL		REL	NIOSH
			STEL			STEL		
Isobutane								
Propane	2,500 ppm		Not available	1,000 ppm		Not available		1,000 ppm
Conditioner	Not available		Not available	Not available		Not available		Not available
High temperature lubricant	Not available		Not available	Not available		Not available		Not available

**Section 09: PHYSICAL AND CHEMICAL PROPERTIES**

Physical State..... Liquid.  
 Physical Appearance..... Light Brown.  
 Odour..... Amine Odour.  
 Odour Threshold (ppm)..... Not available.  
 pH..... Not applicable.  
 Vapour Pressure (psig)..... 60-70 .  
 Vapour Density (Air=1)..... Not available.  
 Evaporation Rate (n-Butyl Acetate = 1)..... Not available.  
 Initial Boiling Point/Boiling Range (° C)..... 125°C -127°C (257°F - 260.6°F).  
 VOC Content..... > 75%.  
 Specific Gravity (Liquid)..... 0.740 - 0.780.  
 Specific Gravity (Aerosol)..... 0.980-1.020 .  
 Solubility in water..... Not soluble in water.  
 Aerosol Flame Projection..... Not available .  
 Auto Ignition Temperature (Propellant), ° C.. 460 °C/860 °F.  
 Flashback..... No data .  
 Flash Point (° C), Method..... -83.15°C/ -117.7°F.  
 Lower Flammable Limit (% Vol)..... 1.8.  
 Upper Flammable Limit (% Vol)..... 9.5.

**Section 10: STABILITY AND REACTIVITY**

Stability..... Stable at normal temperatures and pressures.  
 Incompatibility..... Strong oxidizing agents. Strong acids.  
 Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge.  
 Hazardous Products of Decomposition..... Thermal decomposition and burning may produce carbon monoxide and carbon dioxide.  
 Hazardous Polymerization..... Has not been reported.

**Section 11: TOXICOLOGICAL INFORMATION**

Route of Exposure..... Skin contact, Eye contact, Inhalation.  
 Effects of Acute Exposure..... Rapid released of gases which are liquids under pressure may cause frost burns of exposed tissues (skin,eye) due to evaporative cooling. High gas concentrations will displace available oxygen from the air; unconsciousness and death may occur suddenly from lack of oxygen. Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.  
 Effects of Chronic Exposure..... May cause damage to the central nervous system .  
 Carcinogenicity of Material..... Not classified as carcinogenic by ACGIH, IARC, OSHA or NTP.  
 Reproductive Effects..... No information is available, and no adverse effects are expected.

PRODUCT: Emzone 12A A/C System Conditioner - 114g

CODE: 045855

**Section 11: TOXICOLOGICAL INFORMATION**

Teratogenicity..... No information is available, and no adverse effects are expected.  
 Mutagenicity..... No information is available, and no adverse effects are expected.  
 Toxicological Data

Ingredients	LC50	LD50
Isobutane	NOT INDICATED	NOT INDICATED
Propane	>800,000 ppm (15 min,Inh.rat)	Not available
Conditioner	Not available	Not available
High temperature lubricant	Not available	Not available

**Section 12: ECOLOGICAL INFORMATION**

Environmental..... Physical properties indicate that petroleum gases will rapidly volatilise from the aquatic environment and that acute and chronic effects would not be observed in practice. Complete information is not yet available.

**Section 13: DISPOSAL CONSIDERATIONS**

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

**Section 14: TRANSPORT INFORMATION**

TDG (Canada- Road)..... AEROSOLS, Class 2.1, UN1950.  
 DOT (US-Road)..... AEROSOLS, Class 2.1, UN1950, LTD. QTY. OR ORM-D.  
 IATA (International- Air)..... AEROSOLS, Class 2.1, UN1950, LTD QTY.  
 IMDG (International- Marine)..... AEROSOLS, Class 2.1, UN1950.

**Section 15: REGULATORY INFORMATION**

Canada..... WHMIS Classification. A: Compressed gas. B1: Flammable Gas.  
 USA..... Environmental Protection Act: Constituents of this product are included on the TSCA inventory. OSHA (29CFR 1910.1200) Classification: Compressed Gas. HIMS Classifications: see section 01.

**Section 16: OTHER INFORMATION**

Disclaimer..... The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Empack assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. THIS SDS IS VALID FOR THREE YEARS.

Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHIMIS: Workplace Hazardous Materials Information System.

Prepared by ..... Regulatory Affairs  
 Preparation Date..... Oct24/13  
 Last Revision Date ..... Sep17/14