

**empack**Empack Spraytech Inc.  
98 Walker Drive  
Brampton, Ontario, L6T 4H6  
Canada  
905-792-6571**PRODUCT: Emzone 12A A/C Refrigerant Cylinder - 5.4 kg****CODE: 045899****Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product Identity..... Emzone 12A A/C Refrigerant Cylinder - 5.4 kg  
 Product Item Numbers..... 045899  
 Manufactured by..... Empack Spraytech Inc.  
 98 Walker Drive  
 Brampton  
 Ontario  
 Canada  
 L6T 4H6  
 905-792-6571  
 24 hour emergency telephone number..... CANUTEC: (613)-996-6666 collect.  
 Recommended Use..... Environmental friendly Refrigerant.  
 Consumer Commodity..... Yes.  
 Hazard Ratings:  
 HMIS..... Health: 1 Fire: 4 Reactivity: 1.  
 NFPA Rating..... Health: 1 Fire: 4 Reactivity: 1.

**Section 02: HAZARDS IDENTIFICATION**

Emergency Overview..... Extremely flammable . Container is under pressure. Container may explode if heated. Do not puncture. Do not burn. Contact with rapidly expanding gases can cause frostbite .  
 Potential Health Effects:  
 Skin Contact..... Contact with rapidly expanding gas may cause burns and frostbite. Skin may be flushed; as frostbite develops. Blisters may develop.  
 Eye Contact..... Direct contact with rapidly expanding gas or frost particles may produce severe and possibly permanent eye damage.  
 Ingestion..... Ingestion is not a likely route of exposure.  
 Inhalation..... Acts as a simple asphyxiant.

**Section 03: COMPOSITION/INFORMATION ON INGREDIENTS**

Hazardous Ingredients	CAS #	Wt. %
Propane	74-98-6	30- 60
Isobutane	75-28-5	30- 60

**Section 04: FIRST AID MEASURES**

Eye Contact..... If eye tissue is frozen, seek medical attention immediately. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation, pain, swelling, lacrimation, or photophobia persist, get medical attention as soon as possible .  
 Skin Contact..... If frostbite has occurred, seek medical attention immediately; do NOT rub the affected areas or flush them with water. In order to prevent further tissue damage, do NOT attempt to remove frozen clothing from frostbitten areas. If frostbite has NOT occurred, immediately and thoroughly wash contaminated skin with soap and water.  
 Ingestion..... As this product is a gas, refer to the inhalation section.  
 Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance. If breathing is difficult, give oxygen and get medical attention.  
 Additional Information..... Note to the doctor; treat symptomatically.

**Section 05: FIRE FIGHTING MEASURES**

Flammability Class..... Extremely Flammable.  
 Extinguishing Media..... Use media suitable to the surrounding fire such as foam, dry chemical or water fog.  
 Sensitivity to Mechanical Impact..... Not expected to be sensitive.  
 Sensitivity to Static Discharge..... Not expected to be sensitive.

**Section 06: ACCIDENTAL RELEASE MEASURES**

Spills and Leaks..... Asphyxiant-lack of oxygen can kill. Immediately evacuate all personnel from danger area. Use self-contained breathing apparatus and protective clothing. Shut off leak if without risk. Ventilate area of leak or move cylinder to a well-ventilated area. Remove flames and heating elements. Soak up with absorbent such as vermiculite, sand, or earth. Contain the spill.

PRODUCT: Emzone 12A A/C Refrigerant Cylinder - 5.4 kg

CODE: 045899

**Section 07: HANDLING AND STORAGE**

Handling..... Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling. Use with adequate ventilation. Do not store in temperatures above 120°F (50°C).

**Section 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Eye/Type..... Wear appropriate eye protection to prevent eye contact with the liquid that could result in burns or tissue damage from frostbite .

Skin/Type..... Compressed gases may create low temperatures when they expand rapidly. Leaks and uses that allow rapid expansion may cause a frostbite hazard. Wear appropriate personal protective clothing to prevent the skin from becoming frozen .

Respiratory/Type..... Use approved NIOSH respirators for emergencies.

Engineering Controls..... Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved.

## Exposure Limits

Ingredients	TWA	ACGIH TLV		PEL	OSHA PEL		REL	NIOSH
			STEL			STEL		
Propane	2,500 ppm		Not available	1,000 ppm		Not available		1,000 ppm
Isobutane								

**Section 09: PHYSICAL AND CHEMICAL PROPERTIES**

Physical State..... Gas.

Physical Appearance..... Colorless gas.

Odour..... Gasoline like or natural gas odor .

Odour Threshold (ppm)..... Not available.

pH..... Not applicable.

Vapour Pressure (psig)..... 80- 95 .

Vapour Density (Air=1)..... 1.64.

Evaporation Rate (n-Butyl Acetate = 1)..... Rapid .

Boiling Point (° C)..... -37.8.

VOC Content..... 100%.

Specific Gravity (Liquid)..... 0.520- 0.540.

Specific Gravity (Aerosol)..... Not applicable.

Solubility in water..... Not soluble in water.

Aerosol Flame Projection..... Not applicable.

Auto Ignition Temperature (Propellant), ° C..... Not applicable.

Flashback..... No.

Flash Point (° C), Method..... -83.15°C/ -117.7°F.

Lower Flammable Limit (% Vol)..... 1.8.

Upper Flammable Limit (% Vol)..... 9.1.

**Section 10: STABILITY AND REACTIVITY**

Stability..... Stable at normal temperatures and pressures.

Incompatibility..... Strong oxidizing agents. Strong acids.

Hazardous Products of Decomposition..... Under normal conditions of storage and use, hazardous decomposition products should not be produced . This product may produce carbon monoxide with a deficiency of oxygen .

Hazardous Polymerization..... Has not been reported.

**Section 11: TOXICOLOGICAL INFORMATION**

Route of Exposure..... Skin contact, Eye contact, Inhalation.

Effects of Acute Exposure..... Contact with skin and eyes may cause mild to moderate irritation and frostbite. Symptoms may include redness, pain, numbness, pricking and itching. May cause frostbite .

Effects of Chronic Exposure..... May cause skin defatting and dermatitis.

Carcinogenicity of Material..... Not classified as carcinogenic by ACGIH, IARC, OSHA or NTP.

Reproductive Effects..... No information is available, and no adverse effects are expected.

Teratogenicity..... No information is available, and no adverse effects are expected.

Mutagenicity..... No information is available, and no adverse effects are expected.

## Toxicological Data

Ingredients	LC50	LD50
Propane	>800,000 ppm (15 min,Inh.rat)	Not available
Isobutane	NOT INDICATED	NOT INDICATED

PRODUCT: Emzone 12A A/C Refrigerant Cylinder - 5.4 kg

CODE: 045899

**Section 12: ECOLOGICAL INFORMATION**

Environmental..... Complete information is not yet available.

**Section 13: DISPOSAL CONSIDERATIONS**

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

**Section 14: TRANSPORT INFORMATION**

TDG (Canada- Road).....	LIQUEFIED PETROLEUM GASES, Class 2.1, UN1075.
DOT (US-Road).....	Liquefied petroleum gases, Class 2.1, UN1075.
IMDG (International- Marine).....	Liquefied petroleum gases, Class 2.1, UN1075.
IATA (International- Air).....	Liquefied petroleum gases, Class 2.1, UN1075.

**Section 15: REGULATORY INFORMATION**

Canada.....	WHMIS Classification. A: Compressed gas. B: Flammable and combustible gas.
USA.....	Environmental Protection Act: Constituents of this product are included on the TSCA inventory. OSHA (29CFR 1910.1200) Classification: Compressed Gas. HIMS Classifications: see section 01.

**Section 16: OTHER INFORMATION**

Disclaimer.....	The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Empack assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. THIS SDS IS VALID FOR THREE YEARS.
Abbreviations.....	ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHIMIS: Workplace Hazardous Materials Information System.
Prepared by .....	Regulatory Affairs
Preparation Date.....	Oct24/13
Last Revision Date .....	Sep17/14