

Empack Spraytech Inc. 98 Walker Drive Brampton, Ontario, L6T 4H6 Canada 905-792-6571

PRODUCT: Emzone Air Duster - 284 g CODE: P7-047020

#### **SECTION 01: IDENTIFICATION**

P7-047020 Product Item Numbers.....

Product Identity..... Emzone Air Duster - 284 g Empack Spraytech Inc. 98 Walker Drive Manufacturer.....

Brampton Ontario Canada

L6T 4H6 905-792-6571

In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800) 24 hour emergency telephone number.....

424-9300.

Cleans computers, keyboards, printers, electronics, cameras, audio/video products, faxes, telephones, office equipment, and automobiles. Recommended Use.....

Chemical Family..... 1,1-Difluoroethane.

#### SECTION 02: HAZARD IDENTIFICATION



Label Elements: Signal Word...... WARNING.

Hazard Classification:

Physical Hazards..... Gases Under Pressure - Liquefied Gas .

Health Hazards..... Not Classified. Environmental Hazards..... Not Classified.

Hazard Statement..... H280:Contains gas under pressure; may explode if heated (C).

Precautionary Statements: Prevention..... None.

and delayed

Response..... None . P410+P403:Protect from sunlight. Store in a well-ventilated place. Storage.....

P501:Dispose of contents/container in accordance with local, regional, national, and/or Disposal.....

international regulations.

May be harmful if inhaled. Avoid inhalation of the product. Non-flammable product. However, content in liquid form is flammable. Hazard(s) not otherwise classified (HNOC)

Classified according to:.... Not defined as a flammable aerosol under the Canadian Controlled Product Regulation SOR/88-66, 40 Division 5 criteria. Not defined as flammable aerosol according to 16 CFR

1500.3(c)(6) for the U.S. Federal Hazard Substance Act of the Consumer Product Safety Commission regulations. Heat of combustion is <20 kJ/g and ignition distance is <15 cm.

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS					
HAZARDOUS INGREDIENTS	CAS#	WT. %			

1,1-Difluoroethane 75-37-6 100

## **SECTION 04: FIRST-AID MEASURES**

If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain Inhalation..... immediate medical assistance. Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 Skin Contact..... minutes. Consult a poison control centre or physician immediately. Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs. Eye Contact.....

Ingestion is unlikely to occur. If swallowed do not induce vomiting because of risk of Ingestion.....

aspiration into the lungs. If aspiration is suspected obtain immediate medical attention. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain. Most important symptoms/effects, acute ...





# PRODUCT: Emzone Air Duster - 284 g

## **SECTION 04: FIRST-AID MEASURES**

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

CODE: P7-047020

MIOSH

## **SECTION 05: FIRE-FIGHTING MEASURES**

General Fire Hazards..... Non-flammable product. However, content in liquid form is flammable. Suitable Extinguishing Media..... Dry chemical powder. Carbon dioxide. Foam, water spray or fog. Unsuitable Extinguishing Media..... Do not use water jet as an extinguisher, as this will spread the fire

Specific Hazards Arising from the Chemical In case of fire, the following can be released: Carbon Oxides (CO, CO2), Other unidentified

Organic Compounds. Special Protective Equipment and .........

Precautions for Firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

## **SECTION 06: ACCIDENTAL RELEASE MEASURES**

Personal Precautions, Protective ..... **Equipment and Emergency Procedures** 

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).

Methods and Materials for Containment .. and Cleaning Up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Environmental Precautions.....

Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

## **SECTION 07: HANDLING AND STORAGE**

Precautions for Safe Handling.....

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas.

Conditions for Safe Storage including any Incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

OSHA DEI

#### SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	STEL	PEL	STEL	REL	
1,1-Difluoroethane	Not available	Not available	Not available	Not available	Not available	
Appropriate Engineering	ering Controls Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved.					
Individual Protection Me Eye/Face Protection Skin Protection Respiratory Protection Thermal Hazards						
General Hygiene Consid		When using, do not eat, d such as washing after har Routinely wash work cloth	ndling the material	and before eating, drinki		

## **SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Aerosol. Physical Appearance..... Clear- Colorless. Odor..... Ether odor. Odor Threshold (ppm)..... Aerosol Vapour Pressure (psig, 21°C)..... 110-170.



ACCIH TI V

CODE: P7-047020

## PRODUCT: Emzone Air Duster - 284 g

## SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity ...... Vapour Density (Air=1)..... 0.910-0.970. pH.....Boiling Point liquid (°C)..... -25.0°C (-13.0°F). Melting/Freezing Point (°C)..... -117 °C (-179 °F) - lit. <-50°C (<-58°F). Flash Point (°C), Method..... Flashback.....Evaporation Rate (n-Butyl Acetate = 1)..... Not applicable. VOC Content..... N/A Solubility in water..... Slightly soluble. Auto Ignition Temperature (°C)..... 440. (Liquid). Aerosol Flame Projection..... Lower Flammable Limit (% Vol)..... Upper Flammable Limit (% Vol)..... 16.9. Coefficient of Water/Oil Distribution...... N/A. Viscosity..... N/A.

#### **SECTION 10: STABILITY AND REACTIVITY**

Product not reactive under normal conditions of use. Reactivity Chemical Stability..... Material is stable under normal conditions. Possibility of Hazardous Reactions..... Will not occur. Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge. Incompatible Materials..... Keep away from heat. Strong oxidizing agents. Hazardous Decomposition Products...... See Section 05.

#### SECTION 11: TOXICOLOGICAL INFORMATION

**INGREDIENTS** LC50 LD50

176 mg/L (Rat - 4 hrs) 1,1-Difluoroethane Not available

Routes of entry - Inhalation..... Nο Routes of entry - Skin Absorption..... No. Symptoms Related to the Physical,

Information on Likely Routes of Exposure:

Chemical and Toxicological Characteristics Acute Toxicity.....

Skin Corrosion/Irritation..... N/A. Serious Eye Damage/Eye Irritation..... N/A.

Respiratory or Skin Sensitization.....

Germ Cell Mutagenicity.....

Carcinogenicity.....

Reproductive Toxicity..... STOT - Single Exposure.....

STOT - Repeated Exposure..... Aspiration Hazard..... Chronic Effects..... Prolonged inhalation may be harmful.

Contact with liquid may cause frostbite.

Inhalation: Vapors have a narcotic effect and may cause headache, fatique, dizziness and nausea. Prolong inhalation may be harmful.

N/A.

No data available to indicate product or any components present at greater than 0.1% are mutagenic. None of the ingredients are listed as possibly carcinogenic to humans by IARC or ACGIH.

No information is available.

Not classified. Not classified. Not classified.

May cause damage to the Central Nervous System through prolonged or repeated exposure. Symptoms of overexposure are dizziness, headache, tiredness, nausea,

unconsciousness.

#### **SECTION 12: ECOLOGICAL INFORMATION**

This product contains the following substances which is hazardous for the environment: 1,1-difluoroethane: Fish (Various) LC50-295.783 mg/l (96h), Daphnia magna Ecotoxicity.....

EC50-146.695 mg/l (48h).

The product itself has not been tested. Persistence and degradability ..... Bioaccumulation Potential..... The product itself has not been tested. Mobility in Soil..... The product itself has not been tested.

Other Ádverse Effects..... None Known.



## PRODUCT: Emzone Air Duster - 284 g

## **SECTION 13: DISPOSAL CONSIDERATIONS**

This material and its container must be disposed of as hazardous waste. Avoid release to Appropriate Disposal Methods..... the environment. Spilled material and water rinses are classified as chemical waste and

must be disposed of in accordance with current local, provincial and federal regulations. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.

CODE: P7-047020

#### SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... AEROSOLS, Class 2.1, UN1950. AEROSOLS, Class 2.1, UN1950. AEROSOLS, Class 2.1, UN1950, LTD QTY. IMDG (International- Marine)..... IATA (International- Air)..... AEROSOLS, Class 2.1, UN1950, LTD QTY, Consumer commodity ORM-D. DOT (US-Road).....

## **SECTION 15: REGULATORY INFORMATION**

WHMIS Classification. A: Compressed gas. D2B: Material causing other toxic Materials. All ingredients listed appear on the Domestic Substances List (DSL). Canada Regulations:.....Canadian Environmental Protection Act ...

(CEPA)

**US Regulations** 

TSCA Inventory Status.....

OSHA..... California Proposition 65..... All components are listed on TSCA

This product is considered hazardous under the Federal OSHA hazard communication standard.

This product does not contain any chemical(s) known to the state of California to cause cancer or reproductivity toxicity.

## **SECTION 16: OTHER INFORMATION**

The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information

required by the CPR. .

ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health Administration-USA; TSCA: Toxic Substances Control Act Abbreviations.....

1976-USA; PEL: Pérmissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.

Regulatory Affairs Prepared by ..... OCT 19/2018 Latest Revision .....