

Empack Spraytech Inc. 98 Walker Drive Brampton, Ontario, L6T 4H6 Canada 905-792-6571

CODE: P7-047072

PRODUCT: Emzone LCD & Plasma Screen Cleaner Foam - 60 g (2 Pack)

SECTION 01: IDENTIFICATION

Emzone LCD & Plasma Screen Cleaner Foam - 60 g (2 Pack) Product Identity.....

Product Item Numbers..... P7-047072

Empack Spraytech Inc. 98 Walker Drive Manufacturer.....

Brampton

Ontario Canada L6T 4H6 905-792-6571

In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800) 24 hour emergency telephone number.....

424-9300. Cleans computer monitors, LCD, LED and television screens. Recommended Use.....

SECTION 02: HAZARD IDENTIFICATION



Label Elements: Signal Word..... WARNING.

Hazard Classification: Physical Hazards..... Aerosols - Category 3. Gases Under Pressure - Liquefied Gas.

Skin Irritation - Čategory 3. Health Hazards.....

Environmental Hazards..... Not Classified.

H229:Pressurised container: May burst if heated (3). H280:Contains gas under pressure; Hazard Statement.....

may explode if heated (L). H316: Causes mild skin irritation.

P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251:Do not pierce or burn, even after use. Prevention.....

P332+P313:If skin irritation occurs: Get medical advice/attention.

Response..... Storage..... P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F.

P403:Store in a well ventilated place.

None.

Precautionary Statements:

Chin Contoot

Hazard(s) not otherwise classified (HNOC) None Known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS					
CHEMICAL NAME AND SYNONYMS	CAS#	WT. %			
Isobutane	75-28-5	5-10			
2-Butoxyethanol	111-76-2	1-5			
Antistatic (and) UV agents	Proprietary	0.1-1			

SECTION 04: FIRST-AID MEASURES

The product is not expected to be skin irritant. However, if irritation persists, wash the
contact skin area with soap and water.
mmediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the
upper and lower eyelids. Get medical attention if irritation persists.
Not likely to be ingested. If occurs, do not give anything by mouth to an unconscious
person. Do not attempt to give anything by mouth to an unconscious person. If victim is
alert and not convulsing, rinse mouth out and give 1/2 to 1 glass of water to dilute material.
DO NOT induce vomiting. If spontaneous vomiting occurs, have victim lean forward with
nead down to avoid breathing in of vomitus, rinse mouth and administer more water.
Obtain medical attention IMMEDIATELY. Do not induce vomiting, get medical attention.
Obtain medical advice.
No specific effects have been reported. Supply fresh air if any irritations persists.

ataul ta la a alcia imitauat I lacciacian it is

PRODUCT: Emzone LCD & Plasma Screen Cleaner Foam - 60 g (2 Pack)

SECTION 04: FIRST-AID MEASURES

Most important symptoms/effects, acute .. and delayed

Direct eye contact may cause temporary eye irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be

CODE: P7-047072

SECTION 05: FIRE-FIGHTING MEASURES

General Fire Hazards.....Suitable Extinguishing Media.....

Unsuitable Extinguishing Media.....

Specific Hazards Arising from the Chemical None known.

Special Protective Equipment and

Precautions for Firefighters

Use as directed. Dry chemical powder. Carbon dioxide. Foam, water spray or fog.

None in particular.

Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from

immediate hazard area if it is safe to do.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions. Protective **Equipment and Emergency Procedures** Methods and Materials for Containment .. and Cleaning Up

Environmental Precautions.....

Ensure adequate ventilation: avoid formation of dust. Wear protective equipment and keep unprotected persons away. Use respiratory protection against the effects of dust.

Contain the spill. Clean up the spill area with detergent and water. Once spilled material has been collected, use rags or other suitable material to clean spill area. Rags should be

properly disposed off.
Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent

environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling.....

Avoid contact with eyes. Avoid breathing vapours or spray mists of this product. Use with

adequate ventilation. Keep away from heat, sparks, and open flames. Store in a cool, dry, well-ventilated area away from incompatible substances. Do not store

Conditions for Safe Storage including any Incompatibilities

in direct sunlight.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	CGIH TLV STEL	OSF PEL	IA PEL STEL	NIOSH REL	
Isobutane	Not available	1,000 ppm	Not available	Not available	Not available	
2-Butoxyethanol	20 ppm	Not available	50 ppm	Not available	Not available	
Antistatic (and) UV agents	Not available	Not available	Not available	Not available	Not available	
Appropriate Engineering Controls Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved. Individual Protection Measures:						
Eye/Face Protection Skin Protection Respiratory Protection		Not normally required.				
Thermal Hazards General Hygiene Consid		None Known.				

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Foam.
Physical Appearance	White.
Odour	No odour.
Odour Threshold (ppm)	Not available.
pH	8.0 - 10.0.
Vapour Pressure (psig)	45-65.
Evaporation Rate (n-Butyl Acetate = 1)	Not available.
Boiling Point (°C)	100.
VOC Content	No data.
Relative Density/Specific Gravity	0.990-1.000.
Solubility in water	Soluble in water

CODE: P7-047072

PRODUCT: Emzone LCD & Plasma Screen Cleaner Foam - 60 g (2 Pack)

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

460°C (860°F). (Isobutane). Auto Ignition Temperature (°C).....

Flash Point (°C), Method..... -82.8. (Ìsobutane). Lower Explosive Limit (%, vol)..... Upper Explosive Limit (%, vol)..... 1.8. (Isobutane). 8.8. (Isobutane).

Viscosity..... No data.

SECTION 10: STABILITY AND REACTIVITY

Product not reactive under normal conditions of use.

Stable at normal temperatures and pressures.

Possibility of Hazardous Reactions..... Will not occur.

Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge.

Incompatible Materials..... Avoid contacting with oxidizers. Hazardous Decomposition Products...... Normal products of combustion.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS LC50 LD50

658 mg/L (Rat - 4 hrs) Isobutane Not available

2-Butoxyethanol 450 ppm (Rat - 4 hrs) 470 mg/kg (Oral - Rat)

Antistatic (and) UV agents Not available Not available

Information on Likely Routes of Exposure: Routes of entry - Inhalation..... No.

Routes of entry - Skin & Eye..... Yes. Yes.

2-butoxyethanol may be absorbed through the skin in toxic amounts if contact is repeated

and prolonged. These effects have not been observed in humans.

Symptoms Related to the Physical, Irritant effects.

Chemical and Toxicological Characteristics

Acute Toxicity..... No known significant effects. Skin Corrosion/Irritation..... May cause mild skin irritation.

Serious Eye Damage/Eye Irritation..... Not classified.

Respiratory or Skin Sensitization..... Not expected to be a skin or respiratory sensitizers.

Germ Cell Mutagenicity..... No information is available, and no adverse effects are expected. Carcinogenicity..... Not classified as carcinogenic by ACGIH, IARC, OSHA or NTP. Reproductive Toxicity..... Based on available data, the classification criteria are not met.

STOT - Single Exposure..... Not classified. STOT - Repeated Exposure..... Not classified.

Aspiration Hazard..... Based on available data, the classification criteria are not met.

Chronic Effects..... No long term chronic effects are known or anticipated.

SECTION 12: ECOLOGICAL INFORMATION

May be dangerous for the environment. No data is available on the product itself. Should Ecotoxicity.....

not be released into the environment. The product itself has not been tested. The product itself has not been tested.

Persistence and degradability Bioaccumulation Potential.....

Mobility in Soil..... The product itself has not been tested.

Other Adverse Effects..... None Known.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... UN1950, AEROSOLS, Class 2.2, Ltd. qty.



PRODUCT: Emzone LCD & Plasma Screen Cleaner Foam - 60 g (2 Pack)

SECTION 15: REGULATORY INFORMATION

Canada Regulations:.....

Domestic Substances List (DSL)..... Refer to Section 2 for a WHMIS 2015 Classification for this product. Yes. All substances contained in this product are listed on the TSCA inventory or are exempt. US Regulations.....

SECTION 16: OTHER INFORMATION

Disclaimer..... The information contained herin is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Empack assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abbreviations..... Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act

1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.

CODE: P7-047072

Regulatory Affairs Prepared by Latest Revision 2019-06-06