




Empack Spraytech Inc.  
98 Walker Drive  
Brampton, Ontario, L6T 4H6  
Canada  
905-792-6571

**PRODUCT: Emzone Brake & Parts Cleaner - 390 g**
**CODE: P6-045204**
**SECTION 01: IDENTIFICATION**

Manufacturer..... Empack Spraytech Inc.  
Product Item Numbers..... P6-045204  
Product Identity..... Emzone Brake & Parts Cleaner - 390 g  
24 hour emergency telephone number..... CANUTEC: 1-613-996-6666.  
Recommended Use..... Brake cleaner.

**SECTION 02: HAZARD IDENTIFICATION**

**Label Elements:**

Signal Word..... DANGER.  
Hazard Classification:  
Physical Hazards..... Flammable Aerosols - Category 1. Gases Under Pressure - Compressed gas.  
Health Hazards..... Skin Irritation - Category 3. Eye Damage/Irritation - Category 2A. Specific Target Organ Toxicity, Single Exposure - Category 3. Aspiration Hazard - Category 1.  
Environmental Hazards..... Not Classified.  
Hazard Statement..... H222:Extremely flammable aerosol (1). H229:Pressurized container: may burst if heated (1). H280:Contains gas under pressure; may explode if heated (C). H316:Causes mild skin irritation. H319:Causes serious eye irritation. H335:May cause respiratory irritation. H336:May cause drowsiness or dizziness. H304:May be fatal if swallowed and enters airways.  
Precautionary Statements:  
Prevention..... P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not pierce or burn, even after use. P264+P265: Wash hands thoroughly after handling. Do not touch eyes. P280:Wear eye protection/face protection. P261:Avoid breathing dust/fume/gas/mist/vapours/spray. P271:Use only outdoors or in a well-ventilated area.  
Response..... P332+P317:If skin irritation occurs: Get medical help. P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P317: If eye irritation persists: Get medical help. P304+P340:IF INHALED: Remove person to fresh air and keep comfortable for breathing. P319: Get medical help if you feel unwell. P301+P316: IF SWALLOWED: Get emergency medical help immediately. . P331:Do NOT induce vomiting.  
Storage..... P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. P403+P233:Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.  
Disposal..... P501:Dispose of contents/container in accordance with local, regional, national, and/or international regulations.  
Hazard(s) not otherwise classified (HNOC) Use only as directed.

**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Acetone	67-64-1	80-100
Carbon dioxide	124-38-9	5-10
Naphtha (petroleum), hydro-treated light	64742-49-0	3-7
Isopropyl alcohol	67-63-0	3-7

**SECTION 04: FIRST-AID MEASURES**

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.  
Skin Contact..... Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control centre or physician immediately.  
Eye Contact..... Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if irritation persists.

PRODUCT: Emzone Brake &amp; Parts Cleaner - 390 g

CODE: P6-045204

**SECTION 04: FIRST-AID MEASURES**

Ingestion..... Do not induce vomiting, get medical attention. Rinse mouth. Obtain medical advice.  
 Most important symptoms/effects, acute .. Aspiration hazard.  
 and delayed  
 Indication of immediate medical attention .. Provide general supportive measures and treat symptomatically. In case of shortness of  
 and special treatment needed .. breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be  
 delayed.

**SECTION 05: FIRE-FIGHTING MEASURES**

Suitable Extinguishing Media..... Dry chemical powder. Carbon dioxide. Foam, water spray or fog.  
 Unsuitable Extinguishing Media..... Do not use water jet as an extinguisher, as this will spread the fire.  
 Specific Hazards Arising from the Chemical .. Contents under pressure. Pressurized container may explode when exposed to heat or  
 flame.  
 Special Protective Equipment and .. Firefighters must use standard protective equipment including flame retardant coat, helmet  
 Precautions for Firefighters .. with water to prevent vapor pressure build up. For massive fire in cargo area, use  
 unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.  
 General Fire Hazards..... Extremely flammable aerosol.

**SECTION 06: ACCIDENTAL RELEASE MEASURES**

Personal Precautions, Protective .. No action shall be taken involving any personal risk or without suitable training. Evacuate  
 Equipment and Emergency Procedures .. surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid  
 walking through spilled material. Avoid breathing vapor or mist. Provide adequate  
 ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate  
 personal protective equipment (see Section 08).  
 Methods and Materials for Containment .. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand,  
 and Cleaning Up .. earth, diatomaceous earth, vermiculite) and place in container for disposal according to  
 local/national regulations (see section 13). Eliminate all ignition sources (no smoking,  
 flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.)  
 away from spilled material.  
 Environmental Precautions..... Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent  
 environmental contamination.

**SECTION 07: HANDLING AND STORAGE**

Precautions for Safe Handling..... Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is  
 missing or defective. Do not spray on a naked flame or any other incandescent material.  
 Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut,  
 weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames.  
 Avoid contact with eyes, skin, and clothing. Avoid breathing vapour of this product. Avoid  
 contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas.  
 Conditions for Safe Storage including any .. Store locked up. Pressurized container. Protect from sunlight and do not expose to  
 Incompatibilities .. temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle  
 or store near an open flame, heat or other sources of ignition. Store away from  
 incompatible materials (see Section 10).

**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Acetone	250 ppm	500 ppm	1,000 ppm (2,400 mg/m <sup>3</sup> )	Not available	Not available	Not available
Carbon dioxide	5000 ppm	30000 ppm	9000 mg/m <sup>3</sup>	Not available	STEL: 30000ppm; TWA: 5000ppm	
Naphtha (petroleum), hydro-treated light	353 ppm	Not available	Not available	Not available	Not available	Not available
Isopropyl alcohol	400 ppm (980 mg/m <sup>3</sup> )	500 ppm (1,225 mg/m <sup>3</sup> )	400 ppm (980 mg/m <sup>3</sup> )	500 ppm (1,225 mg/m <sup>3</sup> )	400 ppm (980 mg/m <sup>3</sup> )	
Appropriate Engineering Controls.....	Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved. Ensure that eyewash stations and safety showers are available.					
Individual Protection Measures:						
Eye/Face Protection.....	Do not get in eyes. Wear safety glasses with side-shields.					
Skin Protection.....	Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing.					
Respiratory Protection.....	Use dust and mist respirator.					

PRODUCT: Emzone Brake &amp; Parts Cleaner - 390 g

CODE: P6-045204

**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Thermal Hazards..... None Known.  
 General Hygiene Considerations..... When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.

**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Form..... Aerosol.  
 Physical Appearance..... Spray mist.  
 Odor..... Hydrocarbons.  
 Odor Threshold (ppm)..... 62 ppm. (Acetone).  
 Specific Gravity ..... 0.770-0.790.  
 Vapour Pressure (mm Hg)..... 108-185. (Acetone).  
 Vapour Density (Air=1)..... >1.  
 pH..... Not applicable.  
 Boiling Point liquid (°C)..... >55.  
 Melting/Freezing Point (°C)..... -95.35 - -93.9 °C. (Acetone).  
 Flash point, Liquid (°C), Method..... -18 - -17 °C. (Acetone).  
 Aerosol Ignition Distance..... Ignition Distance of greater than or equal to 75 cm.  
 Flashback..... Yes.  
 Evaporation Rate (n-Butyl Acetate = 1)..... >5.  
 VOC Content..... NMT 10.  
 Solubility in water..... Soluble in water.  
 Auto Ignition Temperature (liquid), °C..... 465-560 °C. (Acetone).  
 Lower Flammable Limit (% Vol)..... 2.5. (Acetone).  
 Upper Flammable Limit (% Vol)..... 14.3. (Acetone).  
 Note..... NMT = Not More Than.

**SECTION 10: STABILITY AND REACTIVITY**

Reactivity ..... Product not reactive under normal conditions of use.  
 Chemical Stability..... Material is stable under normal conditions.  
 Possibility of Hazardous Reactions..... Will not occur.  
 Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge.  
 Incompatible Materials..... Strong oxidizing agents. Strong acids.  
 Hazardous Decomposition Products..... Carbon Oxides.

**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Acetone	71 mg/L (Rat - 4 hrs)	5,800 mg/kg (Oral - Rat); >15,800 mg/kg (Dermal - Rabbit)
Carbon dioxide	Not available	Not available
Naphtha (petroleum), hydro-treated light	33-42 mg/L (Rat - 4 hrs)	>5,800 mg/kg (Oral - Rat); >2,920 mg/kg (Dermal - Rabbit)
Isopropyl alcohol	73 mg/L (Rat - 4hrs)	3,636 mg/kg (Oral - Rat); 4,059 mg/kg (Dermal - Rabbit)

## Information on Likely Routes of Exposure:

Routes of entry - Inhalation..... Yes.  
 Routes of entry - Skin & Eye..... Yes.  
 Routes of entry - Ingestion..... Yes.  
 Routes of entry - Skin Absorption..... No.  
 Symptoms Related to the Physical, ..... Irritant effects.  
 Chemical and Toxicological Characteristics  
 Acute Toxicity..... No known significant effects.  
 Skin Corrosion/Irritation..... Causes mild skin irritation. Prolonged contact may be more irritating.  
 Serious Eye Damage/Eye Irritation..... Causes serious eye irritation.  
 Respiratory or Skin Sensitization..... Not classified.  
 Germ Cell Mutagenicity..... Not classified.  
 Carcinogenicity..... This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.  
 Reproductive Toxicity..... Not classified.  
 STOT - Single Exposure..... Specific target organ toxicity single exposure Category 3. May cause drowsiness and dizziness. May cause respiratory irritation.  
 STOT - Repeated Exposure..... Not classified.  
 Aspiration Hazard..... May be fatal if swallowed and enters airways.

PRODUCT: Emzone Brake &amp; Parts Cleaner - 390 g

CODE: P6-045204

**SECTION 11: TOXICOLOGICAL INFORMATION**

Chronic Effects..... Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

**SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicity..... May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment. This product contains the following substance which may also be hazardous for the environment: Acetone (CAS#: 67-64-1): Toxicity to fish: LC50 >100 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 10294 mg/L, 48 hrs; Toxicity to algae: not available. Naphtha (CAS # 64742-49-0): Toxicity to fish: LC50 4.1 mg/L, 96 hrs; Toxicity to Daphnia: EC50 10 mg/L, 48 hrs; Toxicity to algae: EC50 11 mg/L, 72 hrs; NOEC 0.1 mg/L, 72 hrs. Isopropanol (CAS#: 67-63-0): Toxicity to fish: LC50 9,640 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 5,102 mg/L, 96 hrs; Toxicity to algae: EL50 >2,000 mg/L, 72 hrs.

Persistence and degradability ..... The product itself has not been tested.

Bioaccumulation Potential..... The product itself has not been tested.

Mobility in Soil..... The product itself has not been tested.

Other Adverse Effects..... None Known.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Appropriate Disposal Methods..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty. Dispose in accordance with local, provincial and federal regulations.

**SECTION 14: TRANSPORT INFORMATION**

TDG (Canada- Road)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

DOT (US-Road)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D.

IMDG (International- Marine)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

IATA (International- Air)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

**SECTION 15: REGULATORY INFORMATION**

Canada Regulations:..... Refer to Section 2 for a WHMIS 2015 Classification for this product.

US Regulations

California Proposition 65..... This product is not subject to warning labeling under California Proposition 65.

**SECTION 16: OTHER INFORMATION**

Disclaimer..... The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.

NFPA Storage Level..... Level 3.

Prepared by ..... Regulatory Affairs

Latest Revision ..... 2024-01-24