



Empack Spraytech Inc.
98 Walker Drive
Brampton, Ontario, L6T 4H6
Canada
905-792-6571

PRODUCT: Emzone Exotic Brake Cleaner Pail (Polygrip) - 18.9 L

CODE: P6-045271

SECTION 01: IDENTIFICATION

Manufacturer..... Empack Spraytech Inc.
Product Item Numbers..... P6-045271
Product Identity..... Emzone Exotic Brake Cleaner Pail (Polygrip) - 18.9 L
24 hour emergency telephone number..... CANUTEC: 1-613-996-6666.
Recommended Use..... Brake cleaner.

SECTION 02: HAZARD IDENTIFICATION



Label Elements:
Signal Word..... DANGER.
Hazard Classification:
Physical Hazards..... Flammable Liquids - Category 2.
Health Hazards..... Skin Irritation - Category 3. Eye Damage/Irritation - Category 2A. Specific Target Organ Toxicity, Single Exposure - Category 3. Aspiration Hazard - Category 1.
Environmental Hazards..... Not Classified.
Hazard Statement..... H225:Highly flammable liquid and vapour. H316:Causes mild skin irritation. H319:Causes serious eye irritation. H335:May cause respiratory irritation. H336:May cause drowsiness or dizziness. H304:May be fatal if swallowed and enters airways.
Precautionary Statements:
Prevention..... P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233:Keep container tightly closed. P240:Ground and bond container and receiving equipment. P241:Use explosion-proof electrical/ventilating/lighting equipment. . P242:Use non-sparking tools. P243:Take action to prevent static discharges. P280: Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P264+P265: Wash hands thoroughly after handling. Do not touch eyes. P261:Avoid breathing dust/fume/gas/mist/vapours/spray. P271:Use only outdoors or in a well-ventilated area.
Response..... P303+P361+P353:IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water. P370+P378:In case of fire: Use CO2, dry chemicals or foam to extinguish. P332+P317:If skin irritation occurs: Get medical help. P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P317: If eye irritation persists: Get medical help. P304+P340:IF INHALED: Remove person to fresh air and keep comfortable for breathing. P319: Get medical help if you feel unwell. P301+P316: IF SWALLOWED: Get emergency medical help immediately. . P331:Do NOT induce vomiting.
Storage..... P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. P403+P233:Store in a well-ventilated place. Keep container tightly closed. P235: Keep cool. P405: Store locked up.
Disposal..... P501:Dispose of contents/container in accordance with local, regional, national, and/or international regulations.
Hazard(s) not otherwise classified (HNOC) None Known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Acetone and Oxygenated Solvent Ester Blend	MIXTURE	80-100
Naphtha (petroleum), hydro-treated light	64742-49-0	7-13

SECTION 04: FIRST-AID MEASURES

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.
Skin Contact..... Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control centre or physician immediately.

PRODUCT: Emzone Exotic Brake Cleaner Pail (Polygrip) - 18.9 L

CODE: P6-045271

SECTION 04: FIRST-AID MEASURES

Eye Contact..... Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if irritation persists.

Ingestion..... Do not induce vomiting, get medical attention. Rinse mouth. Obtain medical advice.

Most important symptoms/effects, acute .. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct and delayed contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media..... Dry chemical powder. Carbon dioxide. Foam, water spray or fog.

Unsuitable Extinguishing Media..... Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising from the Chemical Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special Protective Equipment and Firefighters must use standard protective equipment including flame retardant coat, helmet Precautions for Firefighters with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

General Fire Hazards..... Highly flammable liquid and vapour.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective No action shall be taken involving any personal risk or without suitable training. Evacuate Equipment and Emergency Procedures surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).

Methods and Materials for Containment .. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, and Cleaning Up earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Environmental Precautions..... Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling..... Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid contact with eyes, skin, and clothing. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas.

Conditions for Safe Storage including any Incompatibilities Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Acetone and Oxygenated Solvent Ester Blend	250 ppm	500 ppm	1,000 ppm (2,400 mg/m3)	Not available		Not available
Naphtha (petroleum), hydro-treated light	353 ppm	Not available	Not available	Not available		Not available
Appropriate Engineering Controls.....	Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved. Ensure that eyewash stations and safety showers are available.					
Individual Protection Measures:						
Eye/Face Protection.....	Do not get in eyes. Wear safety glasses with side-shields.					
Skin Protection.....	Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing.					
Respiratory Protection.....	Use dust and mist respirator.					
Thermal Hazards.....	None Known.					
General Hygiene Considerations.....	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.					

PRODUCT: Emzone Exotic Brake Cleaner Pail (Polygrip) - 18.9 L

CODE: P6-045271

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Form.....	Liquid.
Physical Appearance.....	Colourless liquid.
Odor.....	Acetone-like.
Odor Threshold (ppm).....	Not available.
Relative Density/Specific Gravity.....	0.780-0.800.
Vapour Pressure (psig).....	Not available.
Vapour Density (Air=1).....	>1.
pH.....	Not applicable.
Boiling Point liquid (°C).....	56°C (133°F). (Acetone).
Melting/Freezing Point (°C).....	-18 - -17 °C (-0.40 - 1 °F). (Acetone).
Flash point, Liquid (°C), Method.....	-18°C. (Acetone).
Aerosol Ignition Distance.....	Not applicable.
Flashback.....	Not applicable.
Evaporation Rate (n-Butyl Acetate = 1).....	>1 .
VOC Content.....	NMT 10.
Solubility in water.....	Miscible in water.
Auto Ignition Temperature (liquid), °C.....	465-560 °C. (Acetone).
Lower Flammable Limit (% Vol).....	2.5. (Acetone).
Upper Flammable Limit (% Vol).....	14.3. (Acetone).
Note.....	NMT = Not More Than.

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Product not reactive under normal conditions of use.
Chemical Stability.....	Material is stable under normal conditions.
Possibility of Hazardous Reactions.....	Will not occur.
Conditions to Avoid.....	Avoid sources of heat and flame, and electrostatic charge.
Incompatible Materials.....	Strong oxidizing agents. Strong acids.
Hazardous Decomposition Products.....	Carbon Oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Acetone and Oxygenated Solvent Ester Blend	71 mg/L (Rat - 4 hrs)	5,800 mg/kg (Oral - Rat); >15,800 mg/kg (Dermal - Rabbit)
Naphtha (petroleum), hydro-treated light	33-42 mg/L (Rat - 4 hrs)	>5,800 mg/kg (Oral - Rat); >2,920 mg/kg (Dermal - Rabbit)

Information on Likely Routes of Exposure:

Routes of entry - Inhalation.....	No.
Routes of entry - Skin & Eye.....	Yes.
Routes of entry - Ingestion.....	Yes.
Routes of entry - Skin Absorption.....	Yes.
Symptoms Related to the Physical,	Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Chemical and Toxicological Characteristics	
Acute Toxicity.....	No known significant effects.
Skin Corrosion/Irritation.....	Causes mild skin irritation. Prolonged contact may be more irritating.
Serious Eye Damage/Eye Irritation.....	Causes serious eye irritation.
Respiratory or Skin Sensitization.....	Not classified.
Germ Cell Mutagenicity.....	No information is available, and no adverse effects are expected.
Carcinogenicity.....	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Reproductive Toxicity.....	Contains no ingredient listed as toxic to reproduction.
STOT - Single Exposure.....	Specific target organ toxicity single exposure Category 3. May cause drowsiness and dizziness. May cause respiratory irritation.
STOT - Repeated Exposure.....	Not classified.
Aspiration Hazard.....	Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.
Chronic Effects.....	No long term chronic effects are known or anticipated. Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

SECTION 12: ECOLOGICAL INFORMATION

PRODUCT: Emzone Exotic Brake Cleaner Pail (Polygrip) - 18.9 L

CODE: P6-045271

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity.....	Harmful to aquatic life. Should not be released into the environment. This product contains the following ingredients: . Acetone (CAS#: 67-64-1): Toxicity to fish: LC50 >100 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 10294 mg/L, 48 hrs; Toxicity to algae: not available . Isopropanol (CAS#: 67-63-0): Toxicity to fish: LC50 9,640 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 5,102 mg/L, 96 hrs; Toxicity to algae: EL50 >2,000 mg/L, 72 hrs. Heptanes including isomers (CAS#: 64742-49-0): Toxicity to fish: LL50 > 13.4 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: EL50 3 mg/L, 48 hrs; Toxicity to algae: EL50 10-30 mg/L, 72 hrs. Chronic Toxicity Daphnia magna: NOEC 0.17 mg/L 21 days.
Persistence and degradability	The product itself has not been tested.
Bioaccumulation Potential.....	The product itself has not been tested.
Mobility in Soil.....	The product itself has not been tested.
Other Adverse Effects.....	None Known.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods.....	This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.
-----------------------------------	---

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road).....	Flammable liquid, n.o.s. (Acetone), Class 3, UN 1993, PG II, Ltd. Qty.
DOT (US-Road).....	Flammable liquid, n.o.s. (Acetone), Class 3, UN 1993, PG II, Ltd. Qty., Consumer commodity ORM-D.
IMDG (International- Marine).....	Flammable liquid, n.o.s. (Acetone), Class 3, UN 1993, PG II, Ltd. Qty.
IATA (International- Air).....	Flammable liquid, n.o.s. (Acetone), Class 3, UN 1993, PG II, Ltd. Qty.

SECTION 15: REGULATORY INFORMATION

Canada Regulations:.....	Refer to Section 2 for a WHMIS 2015 Classification for this product.
Canadian Environmental Protection Act ... (CEPA)	All ingredients listed appear on the Domestic Substances List (DSL).
US Regulations.....	Environmental Protection Act: Constituents of this product are included on the TSCA inventory. This product is considered hazardous under the OSHA Hazard Communication Standard.
California Proposition 65.....	This product is not subject to warning labeling under California Proposition 65.

SECTION 16: OTHER INFORMATION

Disclaimer.....	The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.
Abbreviations.....	ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.
NFPA Storage Level.....	Not applicable.
Prepared by	Regulatory Affairs
Latest Revision	2024-07-26