empack spraytech inc.
Empack Spraytech Inc.
98 Walker Drive
Brampton, Ontario, L6T 4H6
Canada
905-792-6571

PRODUCT: Emzone Bug and Tar Remover - 487 g **CODE: P6-044035**

SECTION 01: IDENTIFICATION

Manufacturer..... Empack Spraytech Inc.
Product Item Numbers..... P6-044035
Product Identity..... Emzone Bug and Tar Remover - 487 g
24 hour emergency telephone number..... CANUTEC: 1-613-996-6666.
Recommended Use..... Bug and tar remover.

SECTION 02: HAZARD IDENTIFICATION



Label Elements:
Signal Word..... DANGER.
Hazard Classification:
Physical Hazards..... Flammable Aerosols - Category 2. Gases Under Pressure - Liquefied Gas.
Health Hazards..... Acute Toxicity Inhalation - Category 5. Skin Irritation - Category 3. Skin Sensitization - Category 1. Specific Target Organ Toxicity, Single Exposure - Category 3. Specific Target Organ Toxicity, Repeated Exposure - Category 1. Aspiration Hazard - Category 1.
Environmental Hazards..... Not Classified.
Hazard Statement..... H222:Extremely flammable aerosol (1). H229:Pressurized container: may burst if heated (1). H280:Contains gas under pressure; may explode if heated (L). H333:May be harmful if inhaled. H316:Causes mild skin irritation. H317:May cause an allergic skin reaction. H335:May cause respiratory irritation. H336:May cause drowsiness or dizziness. H372:Causes damage to organs through prolonged or repeated exposure. H304:May be fatal if swallowed and enters airways.

Precautionary Statements:
Prevention..... P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not pierce or burn, even after use. P264+P265: Wash hands thoroughly after handling. Do not touch eyes. P280:Wear eye protection/face protection. P260:Do not breathe dust/ fume/ gas/ mist/ vapours /spray. P272:Contaminated work clothing must not be allowed out of the workplace. P280:Wear protective gloves. P271:Use only outdoors or in a well-ventilated area. P270:Do not eat, drink, or smoke when using this product.
Response..... P304+P317:IF INHALED: Get medical help. P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P317: If eye irritation persists: Get medical help. P302+P352:IF ON SKIN: Wash with plenty of water. P333+P317: If skin irritation or rash occurs: Get medical help. P362+P364:Take off contaminated clothing and wash it before reuse. P321:For specific treatment see section 4 on this SDS. P304+P340:IF INHALED: Remove person to fresh air and keep comfortable for breathing. P319: Get medical help if you feel unwell. P301+P316: IF SWALLOWED: Get emergency medical help immediately. . P331:Do NOT induce vomiting.
Storage..... P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. P403+P233:Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.
Disposal..... P501:Dispose of contents/container in accordance with local, regional, national, and/or international regulations.
Hazard(s) not otherwise classified (HNOC) None Known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Naphtha (petroleum), hydro-treated light	64742-49-0	10-30
Isobutane	75-28-5	5-10
Petroleum Distillates (Naphtha Hydrotreated Heavy)	64742-48-9	3-7
Propane	74-98-6	1-5
Isopropyl alcohol	67-63-0	1-5
2-Butoxyethanol	111-76-2	1-5

PRODUCT: Emzone Bug and Tar Remover - 487 g **CODE: P6-044035**

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

D-Limonene	5989-27-5	1-5
Distillates (Petroleum) Hydrotreated Light	64742-47-8	1-5

SECTION 04: FIRST-AID MEASURES

Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.
Skin Contact	Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control centre or physician immediately.
Eye Contact	Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if irritation persists.
Ingestion	Do not induce vomiting, get medical attention. Rinse mouth. Obtain medical advice.
Most important symptoms/effects, acute and delayed	Aspiration hazard. Causes damage to organs through prolonged or repeated exposure.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Dry chemical powder. Carbon dioxide. Foam, water spray or fog.
Unsuitable Extinguishing Media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific Hazards Arising from the Chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special Protective Equipment and Precautions for Firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
General Fire Hazards	Flammable Aerosol.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).
Methods and Materials for Containment and Cleaning Up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.
Environmental Precautions	Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid contact with eyes, skin, and clothing. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas.
Conditions for Safe Storage including any Incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	ACGIH TLV TWA	ACGIH TLV STEL	OSHA PEL PEL	OSHA PEL STEL	NIOSH REL
Naphtha (petroleum), hydro-treated light	353 ppm	Not available	Not available	Not available	Not available
Isobutane	Not available	1,000 ppm	Not available	Not available	Not available

PRODUCT: Emzone Bug and Tar Remover - 487 g **CODE: P6-044035**

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	ACGIH TLV TWA	ACGIH TLV STEL	OSHA PEL PEL	OSHA PEL STEL	NIOSH REL
Petroleum Distillates (Naphtha Hydrotreated Heavy)	300 ppm	Not available	500 ppm (2,900 mg/m^3)	Not available	Not available
Propane	Not available	Not available	1,000 ppm	Not available	Not available
Isopropyl alcohol	400 ppm (980 mg/m3)	500 ppm (1,225 mg/m3)	400 ppm (980 mg/m3)	500 ppm (1,225 mg/m3)	400 ppm (980 mg/m3)
2-Butoxyethanol	20 ppm	Not available	50 ppm	Not available	Not available
D-Limonene	Not available	Not available	Not available	Not available	Not available
Distillates (Petroleum) Hydrotreated Light	120 mg/m3	197 ppm	Not established	Not established	Not established

Appropriate Engineering Controls..... Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved. Ensure that eyewash stations and safety showers are available.

Individual Protection Measures:

Eye/Face Protection..... Do not get in eyes. Wear safety glasses with side-shields.

Skin Protection..... Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing.

Respiratory Protection..... Use dust and mist respirator.

Thermal Hazards..... None Known.

General Hygiene Considerations..... When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Form..... Aerosol.
Physical Appearance..... Spray mist.
Odor..... Fragrance.
Odor Threshold (ppm)..... Not available.
Specific Gravity ..... 0.900-0.960.
Vapour Pressure (psig)..... Not available.
Vapour Density (Air=1)..... >1.
pH..... 8-10.
Boiling Point liquid (°C)..... Not available.
Melting/Freezing Point (°C)..... Not available.
Flash Point (°C), Method..... -82.8. Closed cup. (Propellant).
Evaporation Rate (n-Butyl Acetate = 1)..... Not available.
VOC Content..... NMT 40.
Solubility in water..... Soluble.
Aerosol Flame Projection..... >15 cm and <100 cm.
Flashback..... No.
Auto Ignition Temperature (Propellant), °C 460°C (860°F). (Propellant).
Lower Flammable Limit (% Vol)..... 1.8. (Propellant).
Upper Flammable Limit (% Vol)..... 8.8. (Propellant).
Note..... NMT = Not More Than.

SECTION 10: STABILITY AND REACTIVITY

Reactivity ..... Product not reactive under normal conditions of use.
Chemical Stability..... Material is stable under normal conditions.
Possibility of Hazardous Reactions..... Will not occur.
Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge.
Incompatible Materials..... Strong oxidizing agents. Strong acids.
Hazardous Decomposition Products..... Carbon Oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Naphtha (petroleum), hydro-treated light	33-42 mg/L (Rat - 4 hrs)	>5,800 mg/kg (Oral - Rat); >2,920 mg/kg (Dermal - Rabbit)
Isobutane	658 mg/L (Rat - 4 hrs)	Not available

PRODUCT: Emzone Bug and Tar Remover - 487 g **CODE: P6-044035**

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Petroleum Distillates (Naphtha Hydrotreated Heavy)	8500 mg/m3 (Rat - 4hrs)	5000 ppm (Oral - Rat)
Propane	658 mg/L (Rat - 4 hrs)	Not available
Isopropyl alcohol	73 mg/L (Rat - 4hrs)	3,636 mg/kg (Oral - Rat); 4,059 mg/kg (Dermal - Rabbit)
2-Butoxyethanol	450 ppm (Rat - 4 hrs)	470 mg/kg (Oral - Rat)
D-Limonene	Not available	2,000 mg/kg (Oral - Rat)
Distillates (Petroleum) Hydrotreated Light	>1,400ppm (Rat - 4hrs)	>5,000 mg/kg (Oral - Rat); >3.000 mg/kg (Dermal - Rabbit)

Information on Likely Routes of Exposure:

Routes of entry - Inhalation..... Yes.
Routes of entry - Skin & Eye..... Yes.
Routes of entry - Ingestion..... Yes.
Routes of entry - Skin Absorption..... No.
Symptoms Related to the Physical, ... Irritant effects.

Chemical and Toxicological Characteristics

Acute Toxicity..... May be harmful if inhaled.
Skin Corrosion/Irritation..... Causes mild skin irritation.
Serious Eye Damage/Eye Irritation..... Causes serious eye irritation.
Respiratory or Skin Sensitization..... May cause an allergic skin reaction.
Germ Cell Mutagenicity..... No information is available, and no adverse effects are expected.
Carcinogenicity..... This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Reproductive Toxicity..... Not classified.
STOT - Single Exposure..... Specific target organ toxicity single exposure Category 3. May cause drowsiness and dizziness. May cause respiratory irritation.
STOT - Repeated Exposure..... Causes damage to organs through prolonged or repeated exposure.
Aspiration Hazard..... Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.
Chronic Effects..... Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity..... May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment. This product contains the following substance which may also be hazardous for the environment:. Naphtha (CAS # 64742-49-0): Toxicity to fish: LC50 4.1 mg/L, 96 hrs; Toxicity to Daphnia: EC50 10 mg/L, 48 hrs; Toxicity to algae: EC50 11 mg/L, 72 hrs; NOEC 0.1 mg/L, 72 hrs. Isopropanol (CAS#: 67-63-0): Toxicity to fish: LC50 9,640 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 5,102 mg/L, 96 hrs; Toxicity to algae: EL50 >2,000 mg/L, 72 hrs. 2-butoxyethanol (CAS#: 111-76-2): Not established. D-Limonene (CAS#: 5989-27-5): Toxicity to Fish: LC50 0.702 mg/L,96hr; Toxicity to Aquatic Invertebrate: EC50 0.421mg/L, 48hr; Toxicity to Algae: 1.81 mg/L. Distillates, petroleum, hydrotreated light (CAS#: 64742-47-8): Toxicity to fish: LC50 > 45 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: EC50 Not available; Toxicity to algae: EC50 Not available.
Persistence and degradability ..... The product itself has not been tested.
Bioaccumulation Potential..... The product itself has not been tested.
Mobility in Soil..... The product itself has not been tested.
Other Adverse Effects..... None Known.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.
DOT (US-Road)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D.
IMDG (International- Marine)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.
IATA (International- Air)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

PRODUCT: Emzone Bug and Tar Remover - 487 g **CODE: P6-044035**

SECTION 15: REGULATORY INFORMATION

Canada Regulations:.....	Refer to Section 2 for a WHMIS 2015 Classification for this product.
US Regulations	
California Proposition 65.....	This product is not subject to warning labeling under California Proposition 65.

SECTION 16: OTHER INFORMATION

Disclaimer.....	The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.
Abbreviations.....	ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.
NFPA Storage Level.....	Level 2.
Prepared by	Regulatory Affairs
Latest Revision	2025-02-19